

## Quick-Loc Non-woven Discs



Non-Woven Quick-Loc Discs are used for, light deburring, polishing, decorative finishing and blending of all kinds of surfaces in both general and tight spaces.

Available with an option of a plastic male or a female metal, thread button.



### Safety



Quick-Loc Discs perform best between 10-20m/s, this giving the optimum balance between stock removal, surface finish, cutting temperature and wheel life.

**NB!** Excess speed is dangerous and may result in product disintegration, grain shedding and overheating.

**NEVER USE QUICK-LOC DISCS AT SPEEDS IN EXCESS OF 25m/s.**  
Do not use wet or in any coolant or oil.

Use in accordance to ANSI B7.1.

### Standard Sizes Surface Conditioning

Diameter	V-Fine	Fine	Med	Coarse
30mm	●	●	●	●
50mm	●	●	●	●
75mm	●	●	●	●



### Standard Sizes Quick-Strip Disc

Diameter	Coarse
50mm	●
75mm	●



### Standard Sizes Unitized Disc

Diameter	V-Fine	Fine	Med	Coarse
50mm	●	●	●	●
75mm	●	●	●	●



Diameter	Recommended Speed rpm	Maximum Speed rpm
30mm	7000	10000
50mm	5500	7500
75mm	3800	5000

### Disc Holder



Plastic Male

Metal Female

Unitized Discs are available with both Alox and SiC grain.

Available in a Soft, Med and Hard compound.